

Miniature ROM RCBO Consumer Units Datasheet

MCU10/RCBO-MINI, MCU14/RCBO-MINI, MCU18/RCBO-MINI




Construction and Features

- 18th Edition compliant
- Up to 8 useable ways (MCU10), 12 useable ways (MCU14) or 14 useable ways (MCU18)
- Comes with ROM RCBOs of your choice (See part numbers below for quantities)
- Plenty of room for cabling for ease of installation
- LED Illuminated feature LUMO® as standard
- Powder Coated Gloss White
- Pattress available
- 1.2mm Steel
- 40mm Tail entry knockouts
- Multiple Knockouts all round including Rear Entry
- Labels & Instructions
- Accessory pack includes battery

Technical Data

- Rated current: 100A
- Isolator: 100A DP EN60947-3
- Busbar: Floating Insulated Pin Type 100A
- Rated residual operating current: 30mA
- Compatible with MD & MH MCBs
- Neutral Bar: x 1
- Earth Bar: x 1
- Internal Neutral Link: Sleeved flexible heat pressed terminated copper braid
- Conditional Rating: 16KA
- Third Party Tested to EN61439-3 Intertek No 151000012SHA-001/002
- BS7671 Amendment 3 Compliant / Regulation 421.1.201

Overall & Installation Dimensions



Model No	Description	A	B	C
MCU10/RCBO-MINI	8 Useable Way Consumer Unit c/w IS2100 Isolator & 6 ROM RCBOs of your choice.	230	254	110
MCU14/RCBO-MINI	12 Useable Way Consumer Unit c/w IS2100 Isolator & 10 ROM RCBOs of your choice.	230	328	110
MCU18/RCBO-MINI	16 Useable Way Consumer Unit c/w IS2100 Isolator & 14 ROM RCBOs of your choice.	230	398	110

Standard: BSEN61439-3 